

- 7 -

CLAIMS

1. An induction furnace wherein a susceptor made
from an alloy comprising niobium, hafnium and
titanium is positioned within the induction coil
of the furnace.
2. An induction furnace as claimed in claim 1
wherein the alloy susceptor is cylindrical in
shape, the interior surface of the cylinder
forming the lining of the furnace chamber.
3. An induction furnace as claimed in claim 1
wherein the alloy susceptor is cylindrical in
shape and is embedded within a cylinder of a
refractory material, which forms the lining of
the furnace chamber.
4. An induction furnace as claimed in claim 3,
wherein the refractory material is a high purity
alumina.
5. An induction furnace as claimed in claims 3 or 4
wherein the inner surface of the cylinder of
refractory material is formed with one or more
protrusions to assist progress through the
furnace of the material which is being heated by
the furnace.
6. An induction furnace as claimed in claim 5
wherein the protrusion or protrusions are in the
form of one or more helical flanges.
7. An induction furnace as claimed in claim 5 or 6
wherein the cylinder is provided at each end with
a rolling seal.
8. An induction furnace as claimed in any one of

- 8 -

claims 2 to 7 wherein means are provided to rotate the cylinder about its major axis.

- 5 9. An induction furnace as claimed in any one of the preceding claims wherein the induction coil is contained within a gas-tight chamber surrounding the cylindrical wall of the furnace.
- 10 10. An induction furnace as claimed in claim 9 wherein means are provided to fill the gas-tight chamber with nitrogen or inert gas.
- 15 11. An induction furnace as claimed in any one of the preceding claims which is provided at each end with an air lock
- 20 12. An induction furnace as claimed in any one of the preceding claims which also comprises means for precision injection of air, oxygen, water, steam or any other oxidizer or reducing agents such as hydrogen, hydrogen peroxide and hydrochloric acid into the furnace chamber.
- 25 13. An induction furnace as claimed in any one of the preceding claims comprising means for temperature measurement at a plurality of locations within the furnace chamber by detection and measurement of heat radiation from said locations, for the purpose of furnace control.
- 30 14. An induction furnace as claimed in any one of the preceding claims wherein the alloy susceptor further comprises zirconium.
- 35 15. An induction furnace as claimed in claim 14, wherein the alloy susceptor consists of 88% niobium, 10% hafnium, 1% titanium and 1% zirconium.

- 9 -

16. An induction furnace as claimed in claim 1 substantially as herein before described with reference to and as illustrated in the accompanying drawing.

5

17. Use of a furnace as claimed in any one of the preceding claims in the disposal of waste materials, or roasting of ores or minerals.

10